



# USBC CENTER INSPECTION REPORT

## CENTER INFORMATION

REPORT ANNUALLY

Certification Number:	11996	Center Name:	FANGET VIDEO GAMES	Date:	8-20-19
Association Number:		Association Name:		Business Phone:	419 536 0523
Center Manager:	First: RICH	Last: KENNY	Business Phone:		
Center Proprietor:	First: RICH	Last: KENNY	Business Phone:		
Center E-Mail Address:					
Inspection Type:	Annual Inspection: <input type="checkbox"/>	New Installation: <input type="checkbox"/>	Overlay: <input type="checkbox"/>		
Total Lanes:	20	Number of Lanes Added:		Number of Lanes Replaced:	20
Lanes to be Certified:	1-20				

### REPORT WHEN DIFFERENT FROM PREVIOUS INSPECTION

Center Mailing Address:	Street: 2345 DENN RD	City: TOWNVILLE	State: ME	ZIP: 48182
Center Physical Address:	Street: SPAIN	City:	State:	ZIP:
Proprietor's Mailing Address:	Street: SPAIN	City:	State:	ZIP:
Pinsetters: Manufacturer: AMP				
Lane Machine:	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	If yes: Manufacturer: W&A	Model: F&X
Pin Decks:	Wood: <input type="checkbox"/>	Synthetic: <input checked="" type="checkbox"/>	If synthetic: Manufacturer: QUORIC	Model: Q420
Lanes:	Wood: <input type="checkbox"/>	Synthetic: <input checked="" type="checkbox"/>	Multi-Surface: <input type="checkbox"/>	If synthetic: Manufacturer: QUORIC
Resurfaced / Installed By:	Company: QUORIC			
Resurfacer Stencil or Synthetic Model ID Appears On All Lanes:	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	Date resurfaced:	
Wood Lane Top Coat:	Urethane: <input type="checkbox"/>	Water Base: <input type="checkbox"/>	Epoxy: <input type="checkbox"/>	100% Solid: <input type="checkbox"/>
	Guardant: <input type="checkbox"/>	Lane Shield: <input type="checkbox"/>		

# SYNTHETIC LANES



Center Name: FOREST VIEW LANES

Lane Manufacturer: \_\_\_\_\_

Permit Number: \_\_\_\_\_

Distance from Foul Line where measurements taken: Panel 1 \_\_\_\_\_ Panel 2 \_\_\_\_\_ Panel 3 \_\_\_\_\_ Panel 4 \_\_\_\_\_ Panel 5 \_\_\_\_\_

ITEM	Crosswise Tilt, Crowns, & Depressions +/- 0.030" at installation +/- 0.040" annually	Distance from Foul Line where measurements taken: Panel 1 Panel 2 Panel 3 Panel 4 Panel 5														
		Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.					
Synthetic Panel 1 21 7	Crowns (+) & Depressions (-)	Crosswise Tilt:	7	10	10	7	10	10	7	10	10	7	10	10	7	10
		Right 10 board:	0	20	30	-17	20	-16	20	-25	20	-11	-37	20		
		Center 20 board:	-6	14	-3	-18	-11	-26	-11	-10	-35	-28				
Synthetic Panel 2 22 15	Crowns (+) & Depressions (-)	Crosswise Tilt:	7	10	10	7	10	10	7	10	10	7	10	10	7	10
		Right 10 board:	15	15	20	-16	20	-19	15	-10	-16	-31	20			
		Center 20 board:	-11	-28	-6	0	7	-4	3	-26	-25					
Synthetic Panel 3 23 31	Crowns (+) & Depressions (-)	Crosswise Tilt:	7	10	10	7	10	10	7	10	10	7	10	10	7	10
		Right 10 board:	-1	6	14	7	-6	4	-6	11	20					
		Center 20 board:	-11	11	4	-1	-6	-3	-13	6						
Synthetic Panel 4 24 40	Crowns (+) & Depressions (-)	Crosswise Tilt:	7	10	10	7	10	10	7	10	10	7	10	10	7	10
		Right 10 board:	-10	-1	-3	0	7	3	0	-1	10					
		Center 20 board:	-16	-4	-12	-1	-3	-6	-8	7						
Synthetic Panel 5 25 50	Crowns (+) & Depressions (-)	Crosswise Tilt:	7	10	10	7	10	10	7	10	10	7	10	10	7	10
		Right 15 board:	-1	-5	4	-8	-9	-19	20							
		Left 15 board:	6	0	8	-3	-11	9	5	2						

# SYNTHETIC LANES



Center Name: FOREST VIEW LANES

Lane Manufacturer: \_\_\_\_\_

Permit Number: \_\_\_\_\_ Distance from Foul Line where measurements taken: Panel 1 \_\_\_\_\_ Panel 2 \_\_\_\_\_ Panel 3 \_\_\_\_\_ Panel 4 \_\_\_\_\_ Panel 5 \_\_\_\_\_

ITEM	Crosswise Tilt, Crowns, & Depressions +/- 0.030" at installation +/- 0.040" annually	Panel Measurements									
		Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.
Synthetic Panel 1 7	Crowns (+) & Depressions (-)	Crosswise Tilt:	9	10	11	12	12	14	15	16	16
		Right 10 board:	25	20	20	20	20	15	0	20	20
		Center 20 board:	-8	-26	-9	-18	-19	6	-21	-26	-19
		Left 10 board:	-5	-28	-18	+2	-9	11	-26	-20	
		Left 10 board:	-16	-15	-12	+4	-12	11	-28	-25	
	Crowns (+) & Depressions (-)	Crosswise Tilt:	15	0	25	10	20	15	0	15	20
		Right 10 board:	-11	-18	-31	-26	7	-22	-35	-30	
		Center 20 board:	-4	2	-35	-24	9	-15	-32	-35	
		Left 10 board:	0	13	-30	-28	-7	-11	-22	-37	
		Left 10 board:	7	15	20	15	20	30	0	20	
Synthetic Panel 2 15	Crowns (+) & Depressions (-)	Crosswise Tilt:	15	20	15	15	20	30	0	20	
		Right 10 board:	5	-10	-2	-7	18	22	-2	20	
		Center 20 board:	-3	-14	-12	-9	-3	12	-7	15	
		Left 10 board:	-1	-5	-6	-2	24	15	-12	17	
		Left 10 board:	7	15	20	15	20	30	0	20	
	Crowns (+) & Depressions (-)	Crosswise Tilt:	25	25	20	15	15	15	20	20	
		Right 10 board:	0	-10	-11	-8	1	-3	-2	-10	
		Center 20 board:	-8	-18	-19	-12	-10	7	-7	-11	
		Left 10 board:	8	-1	-2	1	+3	3	0	-8	
		Left 10 board:	7	0	18	20	20	20	0	20	
Synthetic Panel 3 31	Crowns (+) & Depressions (-)	Crosswise Tilt:	0	0	0	0	0	0	0	0	
		Right 10 board:	0	-10	-11	-8	1	-3	-2	-10	
		Center 20 board:	-8	-18	-19	-12	-10	7	-7	-11	
		Left 10 board:	8	-1	-2	1	+3	3	0	-8	
		Left 10 board:	7	0	18	20	20	20	0	20	
	Crowns (+) & Depressions (-)	Crosswise Tilt:	0	2.0	1.8	2.0	2.0	2.0	0	2.0	
		Right 15 board:	-6	-9	-6	-12	-14	-10	+2	1	
		Center 20 board:	-3	-5	-7	-13	-6	-8	-3	10	
		Left 15 board:	7	10	10	7	10	7	10	7	
		Left 15 board:	7	10	10	7	10	7	10	7	
Synthetic Panel 4 40	Crowns (+) & Depressions (-)	Crosswise Tilt:	0	2.0	1.8	2.0	2.0	2.0	0	2.0	
		Right 15 board:	-6	-9	-6	-12	-14	-10	+2	1	
		Center 20 board:	-3	-5	-7	-13	-6	-8	-3	10	
		Left 15 board:	7	10	10	7	10	7	10	7	
		Left 15 board:	7	10	10	7	10	7	10	7	
	Crowns (+) & Depressions (-)	Crosswise Tilt:	0	2.0	1.8	2.0	2.0	2.0	0	2.0	
		Right 15 board:	-6	-9	-6	-12	-14	-10	+2	1	
		Center 20 board:	-3	-5	-7	-13	-6	-8	-3	10	
		Left 15 board:	7	10	10	7	10	7	10	7	
		Left 15 board:	7	10	10	7	10	7	10	7	
Synthetic Panel 5 51	Crowns (+) & Depressions (-)	Crosswise Tilt:	0	2.0	1.8	2.0	2.0	2.0	0	2.0	
		Right 15 board:	-6	-9	-6	-12	-14	-10	+2	1	
		Center 20 board:	-3	-5	-7	-13	-6	-8	-3	10	
		Left 15 board:	7	10	10	7	10	7	10	7	
		Left 15 board:	7	10	10	7	10	7	10	7	
	Crowns (+) & Depressions (-)	Crosswise Tilt:	0	2.0	1.8	2.0	2.0	2.0	0	2.0	
		Right 15 board:	-6	-9	-6	-12	-14	-10	+2	1	
		Center 20 board:	-3	-5	-7	-13	-6	-8	-3	10	
		Left 15 board:	7	10	10	7	10	7	10	7	
		Left 15 board:	7	10	10	7	10	7	10	7	

# SYNTHETIC LANES



Center Name: FOREST VIEW

Lane Manufacturer: \_\_\_\_\_

Permit Number: \_\_\_\_\_ Distance from Foul Line where measurements taken: Panel 1 \_\_\_\_\_ Panel 2 \_\_\_\_\_ Panel 3 \_\_\_\_\_ Panel 4 \_\_\_\_\_ Panel 5 \_\_\_\_\_

ITEM	Crosswise Tilt, Crowns, & Depressions +/- 0.030" at installation +/- 0.040" annually	Lane No.		Lane No.		Lane No.		Lane No.		Lane No.		Lane No.	
		7	10	7	10	7	10	7	10	7	10	7	10
Synthetic Panel 1 7	Crowns (+) & Depressions (-)	Right 10 board:	12	18	19	20							
		Center 20 board:	15	10	0	20							
		Left 10 board:	-36	-28	+8	-28							
Synthetic Panel 2 15	Crowns (+) & Depressions (-)	Crosswise Tilt:	20	0	15	20							
		Right 10 board:	-14	-11	-23	-17							
		Center 20 board:	-11	-6	-12	-19							
Synthetic Panel 3 34	Crowns (+) & Depressions (-)	Left 10 board:	-10	-1	-8	-20							
		Crosswise Tilt:	25	25	25	25							
		Right 10 board:	-13	+8	0	0							
Synthetic Panel 4 40	Crowns (+) & Depressions (-)	Center 20 board:	-18	+3	-13	-7							
		Left 10 board:	-12	+8	-3	+9							
		Crosswise Tilt:	0	15	25	20							
Synthetic Panel 5 51	Crowns (+) & Depressions (-)	Right 10 board:	+1	0	-2	-13							
		Center 20 board:	-1	0	-11	-12							
		Left 10 board:	+4	+4	-6	+1							
Synthetic Panel 5 51	Crowns (+) & Depressions (-)	Crosswise Tilt:	0	0	20	15							
		Right 15 board:	+1	+13	+4	-2							
		Left 15 board:	+1	+18	+7	+7							

CENTER NAME: FOODS VILVA LANES

Cent. # 11940



# SECTION A: ANNUAL SPECIFICATIONS

## INSTRUCTIONS:

1. Items 1 through 8 and Section C are to be inspected annually.
2. For tilt measurements circle which side of the level the feeler gauges were placed under.
  - 7 For 7 pin side, 10 for 10 pin side, P for pin deck side, F for foul line side
3. Copy page before inspection for centers with more than 8 lanes.

ITEM	MEASUREMENT	DESCRIPTION	ALL LANES COMPLY?		FAILING LANE NUMBERS	
			Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>
1	AUTOMATIC FOUL DEVICES	Light remains on for 10 to 15 seconds and triggers no more than 1/4" beyond of the approach side of the foul line.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>		
2	LANE PANEL DROP-OFFS	Drop off from trailing to leading edge. Specification: 0.000 - 0.040"	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>		
3	EDGE STRIPS	(FIBER OR SYNTHETIC) Specification: Edge strips must be intact with a smooth, curved edge.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>		
4	PIN SPOTTING	Specification: All pins must stand within their respective pin spots:	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>		

Pin Deck Type (Circle One) Wood or Synthetic If Synthetic: Manufacturer: \_\_\_\_\_

Model: \_\_\_\_\_

ITEM	MEASUREMENT	DESCRIPTION	ALL LANES COMPLY?		FAILING LANE NUMBERS							
			Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>						
5	Kickback Plate to Kickback Plate (at rear row of pins) Spec Range: 59 5/8" 60"		Lane No. 1	Lane No. 2	Lane No. 3	Lane No. 4	Lane No. 5	Lane No. 6	Lane No. 7	Lane No. 8	Lane No. 9	Lane No. 10
			59 3/4"	59 15/16"	59 11/16"	59 11/16"						
2	Crosswise Tilt of Pin Deck (at rear row of pins) Spec Range: -0.040" 0.040"		7	10	7	10	7	10	7	10	7	10
			5	5	0	0						
3	Lengthwise Tilt of Pin Deck Spec Range: -0.187" 0.187"		F	P	F	P	F	P	F	P	F	P
			5	10	5	10						
7	Cutter Depth (at rear row of pins) Spec Range: 3 3/8" 3 5/8"		Between 4-7 pins	Between 6-10 pins	Between 4-7 pins	Between 6-10 pins	Between 4-7 pins	Between 6-10 pins	Between 4-7 pins	Between 6-10 pins	Between 4-7 pins	Between 6-10 pins
			10	7	10	7						
8	Pin Deck Type (Circle One) Wood or Synthetic If Synthetic: Manufacturer: _____ Model: _____		Lane No. 1	Lane No. 2	Lane No. 3	Lane No. 4	Lane No. 5	Lane No. 6	Lane No. 7	Lane No. 8	Lane No. 9	Lane No. 10
			3 1/8"	3 3/8"	3 3/8"	3 3/8"						



CENTER NAME: Foster View

Cart # 11940

# SECTION A: ANNUAL SPECIFICATIONS



## INSTRUCTIONS:

- Items 1 through 8 and Section C are to be inspected annually.
- For tilt measurements circle which side of the level the feeler gauges were placed under.
  - 7 For 7 pin side, 10 for 10 pin side, P for pin deck side, F for foul line side
- Copy page before inspection for centers with more than 8 lanes.

ITEM	MEASUREMENT	DESCRIPTION	ALL LANES COMPLY?		FAILING LANE NUMBERS
			Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
1	AUTOMATIC FOUL DEVICES	Light remains on for 10 to 15 seconds and triggers no more than 1/4" beyond of the approach side of the foul line.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
2	LANE PANEL DROP-OFFS	Drop off from trailing to leading edge. Specification: 0.000 - 0.040"	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
3	EDGE STRIPS	(FIBER OR SYNTHETIC) Specification: Edge strips must be intact with a smooth, curved edge.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
4	PIN SPOTTING	Specification: All pins must stand within their respective pin spots.	Yes: <input type="checkbox"/>	No: <input checked="" type="checkbox"/>	13 15 17 18 14 20

Pin Deck Type (Circle One) Wood or Synthetic If Synthetic: Manufacturer: \_\_\_\_\_

Model: \_\_\_\_\_

ITEM	MEASUREMENT	DESCRIPTION	Lane No.		Lane No.		Lane No.		Lane No.		Lane No.		Lane No.	
			7	10	7	10	7	10	7	10	7	10	7	10
5	Kickback Plate to Kickback Plate (at rear row of pins) Spec Range: 59 5/8" 60"		13	14	15	16	17	18	19	20				
			59 3/4	59 13/16	59 11/16	59 3/4	59 7/8	59 15/16	59 11/16	59 15/16				
6	Crosswise Tilt of Pin Deck (at rear row of pins) Spec Range: -0.040" 0.040"		0	0	5	0	0	5	0	10			10	
3	Lengthwise Tilt of Pin Deck Spec Range: -0.187" 0.187"	Between 4-7 pins	20	20	0	20	20	10	20	5	5	5	5	
7	Between 6-10 pins	Between 6-10 pins	20	20	10	15	10	25	10	5	5	2.5		
5	Cutler Depth (at rear row of pins) Spec Range: 3 3/8" 3 5/8"	7 pin side	3 3/8	3 1/2	3 1/2	3 3/8	3 3/8	3 3/8	3 1/2	3 1/2	3 1/2	3 3/8		
8	10 pin side	10 pin side	3 3/8	3 3/8	3 1/2	3 1/2	3 1/2	3 1/2	3 1/2	3 1/2	3 1/2	3 1/2		

CENTER NAME: Foster View

Cert. # 11940

# SECTION B: NEW INSTALLATIONS, REPLACEMENTS, OR RESURFACING.



## INSTRUCTIONS:

1. Copy page before inspection for centers with more than 8 lanes.
2. Only inspect the affected areas.

ITEM	MEASUREMENT	DESCRIPTION	ALL LANES COMPLY?	FAILING LANE NUMBERS
9	APPROACH DEPRESSIONS	Measured 5" from the approach side of the foul line. Specification: $\pm 0.250"$	Yes: <input checked="" type="checkbox"/> No: <input type="checkbox"/>	
10	APPROACH LENGTH	Length of the approach not including the foul line. Specification: Minimum of 15'	Yes: <input checked="" type="checkbox"/> No: <input type="checkbox"/>	
11	FOUL LINE	Width of the foul line. Specification: $3/8"$ to $1"$	Yes: <input checked="" type="checkbox"/> No: <input type="checkbox"/>	
12	LANE PANEL GAPS	Width of gaps between panels. Specification: Maximum of $0.050"$	Yes: <input checked="" type="checkbox"/> No: <input type="checkbox"/>	
13	LANE LENGTH	Distance from the foul line to the center of the headpin spot. Specification: $60' \pm 1/2"$	Yes: <input checked="" type="checkbox"/> No: <input type="checkbox"/>	
14	PIT DEPTHS	Distance from the pin deck surface to the pin carpet. Specification: Minimum of $43/4"$	Yes: <input checked="" type="checkbox"/> No: <input type="checkbox"/>	
15	PIT LENGTHS	Distance from the rear of the pin deck to the pin curtain. Specification: Minimum 25"	Yes: <input checked="" type="checkbox"/> No: <input type="checkbox"/>	
16	PIN SPOTS	Specifications: Diameters: Center to Center Spacing: $12" \pm 1/16"$	Yes: <input checked="" type="checkbox"/> No: <input type="checkbox"/>	
17	LENGTHWISE TILT OF LANES	Specifications $\pm 0.030"$	Yes: <input checked="" type="checkbox"/> No: <input type="checkbox"/>	

Item	Lane Width (at rear row of pins)		Cutter Width (at rear row of pins) From lane to kickback plate	7 pin side	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.
	41"	42"											
18	Spec Range:		7 pin side	7 pin side	1	2	3	4	5	6	7	8	9
	41"	42"											
19	Spec Range:		7 pin side	10 pin side	1	2	3	4	5	6	7	8	9
	8 3/4"	9 3/8"											
20	Spec Range:		7 pin side	10 pin side	1	2	3	4	5	6	7	8	9
	2 1/2"	3"											

Wood Lane Resurface Date: \_\_\_\_\_



CENTER NAME: Feedis View

Cent. # 11940

# SECTION B: NEW INSTALLATIONS, REPLACEMENTS, OR RESURFACING.



## INSTRUCTIONS:

1. Copy page before inspection for centers with more than 8 lanes.
2. Only inspect the affected areas.

ITEM	MEASUREMENT	DESCRIPTION	ALL LANES COMPLY?	FALLING LANE NUMBERS
9	APPROACH DEPRESSIONS	Measured 5" from the approach side of the foul line. Specification: $\pm 0.250"$	Yes: <input checked="" type="checkbox"/> No: <input type="checkbox"/>	
10	APPROACH LENGTH	Length of the approach not including the foul line. Specification: Minimum of 15'	Yes: <input type="checkbox"/> No: <input type="checkbox"/>	
11	FOUL LINE	Width of the foul line. Specification: $3/8"$ to $1"$	Yes: <input checked="" type="checkbox"/> No: <input type="checkbox"/>	
12	LANE PANEL GAPS	Width of gaps between panels. Specification: Maximum of $0.050"$	Yes: <input checked="" type="checkbox"/> No: <input type="checkbox"/>	
13	LANE LENGTH	Distance from the foul line to the center of the headpin spot. Specification: $60' \pm 1/2"$	Yes: <input checked="" type="checkbox"/> No: <input type="checkbox"/>	
14	PIT DEPTHS	Distance from the pin deck surface to the pin carpet. Specification: Minimum of $47/4"$	Yes: <input checked="" type="checkbox"/> No: <input type="checkbox"/>	
15	PIT LENGTHS	Distance from the rear of the pin deck to the pin curtain. Specification: Minimum 25"	Yes: <input checked="" type="checkbox"/> No: <input type="checkbox"/>	
16	PIN SPOTS	Specifications: Diameters: Center to Center Spacing: $12" \pm 1/16"$	Yes: <input checked="" type="checkbox"/> No: <input type="checkbox"/>	
17	LENGTHWISE TILT OF LANES	Specifications $\pm 0.030"$	Yes: <input checked="" type="checkbox"/> No: <input type="checkbox"/>	

Item	Spec Range	Spec Range	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.
18	41"	42"	5	6	7	8	9	10	11	12	
			41 1/16	41 1/16	41 1/16	41 1/16	41 1/16	41 1/16	41 3/4	41 3/8	
19	0 3/4"	9 3/8"	9	9 1/16	9 1/8	9 1/8	9 1/8	9 1/8	9	9 1/8	
			9 1/16	9 3/16	9 1/8	9 1/8	9 1/8	9 1/8	9 1/8	9 1/8	
20	2 1/2"	3"	10	10	10	10	10	10	10	10	
			2 13/16	2 3/4	2 7/8	2 7/8	2 13/16	2 13/16	2 13/16	2 13/16	

Wood Lane Resurface Date: \_\_\_\_\_

L-11 → 7-2 13/16  
 (20) 10-2 7/8

← 2 3/4  
 2 3/4

CENTER NAME: Forest View Cent. # 11940

# SECTION B: NEW INSTALLATIONS, REPLACEMENTS, OR RESURFACING.



## INSTRUCTIONS:

1. Copy page before inspection for centers with more than 8 lanes.
2. Only inspect the affected areas.

ITEM	MEASUREMENT	DESCRIPTION	ALL LANES COMPLY?	FAILING LANE NUMBERS
9	APPROACH DEPRESSIONS	Measured 5" from the approach side of the foul line. Specification: ± 0.250"	Yes: <input checked="" type="checkbox"/> No: <input type="checkbox"/>	
10	APPROACH LENGTH	Length of the approach not including the foul line. Specification: Minimum of 15'	Yes: <input checked="" type="checkbox"/> No: <input type="checkbox"/>	
11	FOUL LINE	Width of the foul line. Specification: 3/8" to 1"	Yes: <input checked="" type="checkbox"/> No: <input type="checkbox"/>	
12	LANE PANEL GAPS	Width of gaps between panels. Specification: Maximum of 0.050"	Yes: <input checked="" type="checkbox"/> No: <input type="checkbox"/>	
13	LANE LENGTH	Distance from the foul line to the center of the headpin spot. Specification: 60" ± 1/2"	Yes: <input checked="" type="checkbox"/> No: <input type="checkbox"/>	
14	PIT DEPTHS	Distance from the pin deck surface to the pin carpet. Specification: Minimum of 4 3/4"	Yes: <input checked="" type="checkbox"/> No: <input type="checkbox"/>	
15	PIT LENGTHS	Distance from the rear of the pin deck to the pin curtain. Specification: Minimum 25"	Yes: <input checked="" type="checkbox"/> No: <input type="checkbox"/>	
16	PIN SPOTS	Specifications: Diameters: Center to Center Spacing: 12" ± 1/16"	Yes: <input checked="" type="checkbox"/> No: <input type="checkbox"/>	
17	LENGTHWISE TILT OF LANES	Specifications: ± 0.030"	Yes: <input checked="" type="checkbox"/> No: <input type="checkbox"/>	

ITEM	MEASUREMENT	DESCRIPTION	Lane No.							
			13	14	15	16	17	18	19	20
18	Spec Range:	41" - 42"	41 1/16	41 1/16	41 5/8	41 1/16	41 1/16	41 1/16	41 1/16	41 1/16
	Lane Width (at rear row of pins)									
19	Spec Range:	8 3/4" - 9 3/8"	9	9 1/16	9	9 1/16	9 1/16	9 1/16	8 13/16	9 1/16
	Gutter Width (at rear row of pins) From lane to kickback plate									
20	Spec Range:	2 1/2" - 3"	2 7/8	2 13/16	2 3/4	2 13/16	2 7/8	2 7/8	2 13/16	2 1/16
	Center of Corner Pin to Gutter Edge									

Wood Lane Resurface Date: \_\_\_\_\_